



# MYP-36US

## POLYESTER FILM TAPE – BLUE COLOR

### DESCRIPTION:

MYP-36US is constructed with a 2 mil Polyester Film and coated with 1.5 mil residue-free silicone adhesive. It is one of the cleanest and strongest splicing tapes available with high tack and high adhesion. Bonds well to treated papers, films, foils, etc. Good chemical and heat resistance. Meets UL510 Class B (130°C / 266°F).

### APPLICATIONS:

- Splicing siliconized papers, films, and non-woven materials in converting.
- Masking tape in powder coating applications, etc.

### PHYSICAL PROPERTIES:

Color	Blue
Backing	2.0mil Polyester Film
Adhesive	1.5mil Silicone
Total Thickness	3.5mil
Adhesion to Steel	35 oz/inch
Tensile Strength	44 lbs/inch
Elongation	100%
Dielectric Strength	6.0 kV
Temperature Range	-100°F to 350°F

**NOTE:** The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

(1401SH2525)